

WORK INSTRUCTION

Gratch SRA Shadow Remover

Revision: 2021.1

Product description

Graffiti shadow remover, applicable on every alkali resistant surface, porous as well as smooth. Not biodegradable. Applicable on concrete, brick, marble, and other mineral surfaces). Works fast and effectively.

Technical properties

Colour	brown
Density	1,26
pH-value	14 (undiluted)
Usage	4 - 15 m ² / ltr

Instructions for use

GRATCH SRA may be diluted with water (max. 1:10), depending on the cleaning power needed. In most cases use purely.

Smear the shadows on the surface with GRATCH SRA and a brush. Leave it to work 1 to 3 minutes (depending on kind of surface). Squirt off the graffiti shadows with hot water under high pressure.

On rough non-smooth surfaces like brick, squirt from different angles. If necessary please repeat the cleaning-procedure.

Always test a small area before you start.

ATTENTION: CORROSIVE PRODUCT!!

Packaging

1 - 10 liter cans

Cleaning materials

After use rinse the materials with plenty water

Storage and shelf life

Shelf life is unopened minimal 24 months

Store frostfree in a dry and cool place

Keep container tightly closed



Quality and safety regulations

Read safety instructions before use (MSDS). Keep out of reach of children.

The effectiveness of this system is based upon years of practical experience and laboratory research. The manufacturer / supplier guarantees that the quality of the work meets the characteristics that were promised by the manufacturer / supplier, if the provided instructions are adhered to and the work has been executed according to the requirements of skilled workmanship. The manufacturer / supplier is not liable if the final result is affected in a negative way by factors that are uncontrollable. The buyer must check with the regular means available to him if the supplied products are suitable for the intended application.

Supplier

Gratch International
P.O. Box 7034
5980 AA Panningen
The Netherlands
info@gratch.com
+31 77 465 1095