

WORK INSTRUCTION: *Alu & Ano Quick Protector*

RV-11

Revision: 2010.1

Product description

Protects aluminium and also removes slight contamination. Simple, fast reconditioner for periodic treatment. Restores colour and lustre. Ready to use.

Advantages

Why is Alu & Ano Quick Protector better than other conservatives:

1. Removes light contamination and protects surface in one treatment.
2. Easy and fast to work with.
3. Rinsing or neutralising not necessary.
4. Water not necessary.
5. Easy to use if you want to recondition the surface again.
6. Non-aggressive, it does not damage other façade materials.

Technical properties

Colour	transparant
Specific gravity	0,8
PH-value	undetermined
Usage	40 m ² / ltr.

Applicable surfaces

Virtually all types of aluminium and metal.

Reaction system

Conservation is activated based on chemical and mechanical processing.

Processing temperature

Between 5°C and 35°C.

Pre-treatment

Surface must be free of dust and sand.

Advice: first test a small area to see if the result meets the expectations.

Instructions for use

Please note: do not use in freezing temperatures or high humidity. Alu & Ano Quick Protector RV-11 contains a silicon emulsion. When other Alu Protectors are applied, the pre-cleaning must be adjusted to the extent that all silicones are removed.

Shake well before use. Apply undiluted with a soft cloth. Wait a while, manually spread Alu & Ano Quick Protector RV-11 with a dry cloth until the surface has an even lustre. Use only in well-ventilated areas.

Packaging

1000 ml. bottles.

Storage and shelf life

Shelf life is unopened minimal 12 months.

Store frostfree in a dry and cool place.

Keep container tightly closed.

Processing thickness

<i>Usage</i>	<i>Thickness</i>	<i>Surface</i>
40 m ² / ltr.	0.0005 mm (wet)	Total average

Warnings



highly flammable



harmful



dangerous for the environment, contains nafta

Quality and safety regulations

Read safety instructions before use (MSDS). Keep out of reach of children. Contains: Nafta
Toxic to aquatic organismus, may cause long-term adverse affects in the aquatic environment.

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. During application wear suitable respiratory equipment. Vapours may cause drowsiness and dizziness. Do not breath vapour. In case of fire, use water.

The effectiveness of this system is based upon years of practical experience and laboratory research. The manufacturer / supplier guarantees that the quality of the work meets the characteristics that were promised by the manufacturer / supplier, if the provided instructions are adhered to and the work has been executed according to the requirements of skilled workmanship. The manufacturer / supplier is not liable if the final result is affected in a negative way by factors that are uncontrollable. The buyer must check with the regular means available to him if the supplied products are suitable for the intended application.