

WORK INSTRUCTION: *Alu Renovator 2-in-1*

RV-15

Revision: 2010.1

Product description

Cleans and renovates enamelled / coated aluminium. pH-neutral, water-based. Cleaning and conservation in 1 renovation technique. Intended for removing scale stains, cement residue, traces of rust, contamination etc. A high-quality conservation remains after cleaning. Removes contamination and protects lacquering in one treatment. Restores colour, lustre and hardness in one treatment. Prevents fast atmospheric and other contamination.

Advantages

Why is Alu Renovator better than other cleaning agents:

1. Cleans and renovates in one treatment.
2. Environment-friendly; water-based; no poisonous fumes, pH-neutral.
3. Not flammable; EcoSafe.
4. Easy and fast to work with.
5. Rinsing or neutralising not necessary.
6. Easy application for spot repair.
7. Water not necessary.
8. No negative residue.
9. Easy to use if you want to recondition the surface again.
10. Non-aggressive, does not damage other facade materials.

Technical properties

Colour	yellow-green
Specific gravity	1,05
PH-value	7,5
Usage	20 m ² / ltr.

Applicable surfaces

Virtually all types of enamelled and coated aluminium.

Alu Renovator RV-15 is also suitable for synthetic materials and PVC surfaces.

Reaction system

Conservation is activated based on chemical and mechanical processing.

Processing temperature

Between 5°C and 35°C.



Pre-treatment

Surface must be free of dust and sand.

Advice: first test a small area to see if the result meets the expectations.

Instructions for use

Shake well before use.

Spread product manually until dirt and stains have disappeared completely. Use a sufficient amount and rub using pressure to fill the pores. Use of a low rpm polishing machine is optional. Excess product can be removed with a dry cloth.

Packaging

1000 ml. bottles.

Storage and shelf life

Shelf life is unopened minimal 12 months.

Store frostfree in a dry and cool place.

Keep container tightly closed.

Processing thickness

<i>Usage</i>	<i>Thickness</i>
20 m ² / ltr.	n/a

Quality and safety regulations

Read safety instructions before use (MSDS). Keep out of reach of children.

The effectiveness of this system is based upon years of practical experience and laboratory research. The manufacturer / supplier guarantees that the quality of the work meets the characteristics that were promised by the manufacturer / supplier, if the provided instructions are adhered to and the work has been executed according to the requirements of skilled workmanship. The manufacturer / supplier is not liable if the final result is affected in a negative way by factors that are uncontrollable. The buyer must check with the regular means available to him if the supplied products are suitable for the intended application.