

WORK INSTRUCTION: *Glass Protector*

RV-05

Revision: 2010.1

Product description

A glass and ceramics ennobling product (water repellent, dirt protection). Ready to use.

Advantages

Why is Glass Protector better than other dirt repellent agents:

1. Pre-cleans without aggressive agents (Glass PreCleaner RV-01).
2. Does not loose material after application.
3. Long-lasting result.
4. Easy and fast to apply.
5. Applicable in household and industrial use.

Technical properties

Colour	transparant
Specific gravity	0,8
PH-value	7
Usage	40 m ² / ltr.

Applicable surfaces

All types of glass.

Reaction system

Chemical drying; refining is activated based on chemical interaction.

Physical drying; solvent.

Processing temperature

Between 10°C and 35°C.

Pre-treatment

Surface must be free of dust and sand.

Advice: first test a small area to see if the result meets the expectations.

Instructions for use

Thoroughly pre-clean existing glass with Glass PreCleaner RV-01.

Shake well before use. Apply Glass Protector RV-05 with a soft cloth, undiluted and even (professional use: spray with fine coat). Spread Glass Protector RV-05 until the glass surface has an even lustre.

When applied to etched or sandblasted glass, crosswise and even application is necessary (e.g. spraying). An even post cleaning is recommended (preferably by mechanical)

If necessary manually or mechanically wash the surface. After refinement of the glass the wash frequency can be lowered. Use only in well-ventilated areas.

Packaging

1000 ml. bottles.

Storage and shelf life

Shelf life is unopened minimal 12 months.

Store frostfree in a dry and cool place.

Keep container tightly closed.

Processing thickness

<i>Usage</i>	<i>Thickness</i>	<i>Surface</i>
40 m ² / ltr.	0,010 mm	Total average

Warnings



highly flammable



harmful

Quality and safety regulations

Read safety instructions before use (MSDS). Keep out of reach of children. Irritating to eyes. Vapours may cause drowsiness and dizziness. During application wear suitable respiratory equipment. Keep away from sources of ignition. No smoking.

The effectiveness of this system is based upon years of practical experience and laboratory research. The manufacturer / supplier guarantees that the quality of the work meets the characteristics that were promised by the manufacturer / supplier, if the provided instructions are adhered to and the work has been executed according to the requirements of skilled workmanship. The manufacturer / supplier is not liable if the final result is affected in a negative way by factors that are uncontrollable. The buyer must check with the regular means available to him if the supplied products are suitable for the intended application.