

WORK INSTRUCTION: *PolyPlast Renovator*

RV-20

Revision: 2010.1

Product description

A polyplast cleaning and renovation product, pH-neutral, water-based. Ready to use. Intended for removing atmospheric contamination, scale, cement residue, rust, decolouration, heavy contamination etc. A high-quality conservation remains after cleaning. Removes dirt and protects the surface in one treatment. Restores colour, lustre and hardness in one treatment. Prevents fast atmospheric and other contamination.

Advantages

Why is PolyPlast Renovator better than other cleaners:

1. Thoroughly cleans in one treatment.
2. Environment-friendly; water-based; no poisonous fumes, pH-neutral.
3. Not flammable; EcoSafe.
4. Easy and fast to work with.
5. Rinsing or neutralising not necessary.
6. Simple application in case of spot repair.
7. Water not required.
8. No negative residues, does not affect softening agents.
9. Easy to use if you want to recondition the surface again.
10. Non-aggressive, does not damage other facade materials.

Technical properties

Colour	yellow-green
Specific gravity	1,05
PH-value	7,5
Usage	40 m ² / ltr.

Applicable surfaces

Virtually all types of synthetic material, plastics and polyester.
PolyPlast Renovator RV-20 may also be used on lacquered / coated aluminium.

Reaction system

Conservation is activated based on chemical and mechanical processing.



Processing temperature

Between 5°C and 35°C.

Pre-treatment

Surface must be free of dust and sand.

Advice: first test a small area to see if the result meets the expectations.

Instructions for use

Shake well before use. Apply undiluted with a soft cloth. Spread product manually until dirt and stains have disappeared completely. Use a sufficient amount of the product and rub using pressure to fill the pores. The use of a low rpm polishing machine is optional. Excess product can be removed with a dry cloth. Use only in well-ventilated areas.

Packaging

1000 ml. bottles.

Storage and shelf life

Shelf life is unopened minimal 12 months.

Store frostfree in a dry and cool place.

Keep container tightly closed.

Processing thickness

<i>Usage</i>	<i>Thickness</i>	<i>Surface</i>
40 m2 / ltr.	0.0005 mm (wet)	Total average

Quality and safety regulations

Read safety instructions before use (MSDS). Keep out of reach of children.

The effectiveness of this system is based upon years of practical experience and laboratory research. The manufacturer / supplier guarantees that the quality of the work meets the characteristics that were promised by the manufacturer / supplier, if the provided instructions are adhered to and the work has been executed according to the requirements of skilled workmanship. The manufacturer / supplier is not liable if the final result is affected in a negative way by factors that are uncontrollable. The buyer must check with the regular means available to him if the supplied products are suitable for the intended application.